

PROJECT:

DATE:

# LED PANEL LIGHT EDGELIT/SLIM

أوبتيمال لايت  
Optimal Light



MODEL # OPT POXX

## LED ROUND INDOOR DOWN LIGHTS

LED round panel lights are the ideal solution to light up your home, office, showroom etc. It is the most common type of led down lights. You can save up to 80% of power consumption compared to conventional incandescent, Compact Fluorescent lamps. Its smooth glareless brightness is so relaxing and good for eyes. Optimal Light's round panel lights are so unique in its design and specification. Its PMMA component make its output spotless and lasting. We are using branded quality components. Our led chips and driver components are highly efficient and therefore we can guarantee you healthy lighting experience.




# EPISTAR

30000H Long life	Not dimmable	Ra ≥ 80 CRI	> 0.9 lamp displacement factor	120° Beam angle	15000x
---------------------	--------------	-------------------	-----------------------------------	--------------------	--------

### Panel Down Light Features

Elegant anti-glare Design  
Voltage: 100-277 AC  
Die casting aluminum and PMMA  
EPISTAR led chips  
Fire resistant quality Driver  
PF : >0.9  
Over Temperature protection  
High index silica gel for encapsulation  
Interated radiator for heat dissipation



	Common cut-out size for an easy switch from conventional halogen spotlights.
	High quality PMMA LGP Not turn yellowish for long time
	Long life LED driver included, Passing EMC & CB Power Factor : > 0.9 220-240V 50/60Hz Lamp displacement factor : > 0.9
	No harmful UV irradiation
	Up to <b>85%</b> Energy saving
	Day light (6500K) Cozy cool white light(4000K) Warm white light (3000K) for wider options, with good color rendering(CRI>80)
	Durable aluminium housing
	Durable, lifespan More than 30,000 hour Service life 5-10 times than Filament Lamp

IECEE C E CB

RoHS COMPLIANT

EMC  
Product ion inspected

عامة الجودة  
SASO  
QUALITY MARK

PROJECT:

DATE:

# LED PANEL LIGHT EDGELIT/SLIM


أوبتيمال لايت  
Optimal Light



MODEL # OPT POXX

## LED ROUND INDOOR DOWN LIGHTS

CODE	DESCRIPTION	WATT	POWER	LUMEN	CCT	SIZE	PF. >	LifeTime
OPT-P033	LED Panel 3"	5	100-277 V	340	3000K	75mm	0.5	30,000
OPT-P034	LED Panel 3"	5	100-277 V	340	4000K	75mm	0.5	30,000
OPT-P036	LED Panel 3"	5	100-277 V	340	6500K	75 mm	0.5	30,000
OPT-P043	LED Panel 4"	9	100-277 V	585	3000K	105mm	0.5	30,000
OPT-P044	LED Panel 4"	9	100-277 V	585	4000K	105mm	0.5	30,000
OPT-P046	LED Panel 4"	9	100-277 V	585	6500K	105mm	0.5	30,000
OPT-P063	LED Panel 5"6"	15	100-277 V	1200	3000K	140mm	0.9	30,000
OPT-P064	LED Panel 5"6"	15	100-277 V	1200	4000K	140mm	0.9	30,000
OPT-P066	LED Panel 5"6"	15	100-277 V	1200	6500K	140mm	0.9	30,000
OPT-P083	LED Panel 8"	18	100-277 V	1440	3000K	200mm	0.9	30,000
OPT-P084	LED Panel 8"	18	100-277 V	1440	4000K	200mm	0.9	30,000
OPT-P086	LED Panel 8"	18	100-277 V	1440	6500K	200mm	0.9	30,000



Note: Input Voltage marked on product is 220-240, But this product's actual Voltage is 100-277 V

IECEE C E CB

RoHS  
COMPLIANT

EMC  
Production inspected

SASO  
QUALITY MARK



30,000 Hours



50/60 Hz



100-270 VAC



IP 20



-20 ~ +45 °C

